THERMO KING

SR-700 Designed for intercity buses

Rooftop, One-piece Compact System

(A)

- Lightweight
- Small in size
- Short installation time
- High-volume fresh air intake option
- Aesthetically appealing



Ingersoll Rand Climate Control Technologies NCI Building - 4th Floor, Culliganlaan 1B, 1831 Diegem, Belgium.

www.thermoking.com

© 2006 Ingersoll-Rand Company Limited TK 60074-3-PL E (8-06)

www.ingersollrand.com

SR-700

The SR-700 is a lightweight compact rooftop air conditioning system. Clever design enables very easy installation. Designed for intercity bus applications. High-volume fresh air intake and different side covers are available as an option.

This new generation of TK units offers a number of advantages over it's predecessor: lower weight (15-18%), reduced height (10%), smaller dimensions (5% shorter).

Controls

ClimaAIRE I D and ClimaAIRE II Control Systems are Thermo King's newest computerised control systems. These systems give the driver total temperature control within the vehicle. Alarm indicators and codes for troubleshooting and maintenance are included, as well as a precise diagnostic system for compressors and system hour meters that allows for effective preventive maintenance.



ClimaAire II



ClimaAire I D

System cooling capacity

- Maximum Capacity:
- Rated Capacity:
- System Heating Capacity: 27 Rated capacities are at following conditions: outside 35 °C, inside 27 °C DB and 19 °C WB

Evaporator airflow

Refrigerant

HFC R-134a

@ 0 inch (0 mm) water column external static pressure

3650 m³/h

Thermo King Asia Pacific

Thermo King Americas Minneapolis, MN U.S.A.

Hong Kong, PRC Tel: + 852 2507 9100 Fax: + 852 2827 5159

Tel: + 1 952 887 2200

Fax: +1 952 887 2529

Thermo King Europe

Kolin, Czech Republic Tel: + 1 420 321 757111 Fax: + 420 321 757170



23 kW



Worldwide service organisation Thermo King backs its equipment

Filectric power requirements 80 amps at 27V DC (cool version) Weight (cool version) Unit 111 kg Compressor TM31 16,7 kg Compressor X430 52 kg n)



