

- High capacity
- High airflow
- Lightweight
- Rooftop, One-piece Compact System
- Short installation time
- Fresh air options







SR 380

The SR 380 provides a number of advantages such as higher capacity, higher airflow, shorter installation time. This new unit in Thermo King product portfolio is lightweight compact rooftop air-conditioning system suitable for shuttle and mini bus applications.

SR 380 has 3 fresh air options: permanent fresh air, fresh air amount controlled by flap, with no fresh air. Due to its low height, it provides elegant appeal on the roof of the bus.





ClimAire I D

System cooling capacity

· Capacity: 10.5 kW

The unit's capacity will vary according to climatic conditions and compressor rpms.

Tropic version available

System heating capacity

• 12 kW

Evaporator airflow

@ 0 inch (0 mm) water column external static pressure:

• 1900 m³/h

Refrigerant

• HFC R-134a

Electric power requirements

• 57 A at 13.5V DC (cool version)

• 33 A at 27V DC (cool version)

Weight (cool version)

· Unit: 65 kg

Compressor: TM16 7.1 kg

Unit Dimension (in mm)

Length: 1885Width: 1498Heigth: 197

Worldwide service organisation

Thermo King backs its equipment and customers with a highly trained, worldwide service organisation. This assures you the support of factory authorised service and shop facilities, a stock of factory parts and factory trained mechanics.

Thermo King Europe

Kolin, Czech Republic Tel: + 420 321 757111 Fax: + 420 321 757170

Hockenheim, Germany Tel: +49 6205 2024 0 Fax: +49 6205 2024 55

Thermo King Americas

Minneapolis, MN U.S.A. Tel: +1 952 887 2200 Fax: +1 952 887 2529

Thermo King Asia Pacific

Hong Kong, PRC Tel: +852 2507 9100 Fax: +852 2827 5159

Thermo King do Brasil

São Paulo, Brasil Tel: +55 11 3049 8900 Fax: +55 11 3842 3924



www.ingersollrand.com www.thermoking.com

Ingersoll Rand Climate Control Technologies NCI Building - 4th Floor, Culliganlaan 1B, 831 Diegem, Belgium.